



alternatives in terms of stability, quality, consistency and appearance.

- **Real timber** substrate
- Strong bond
- **Premium finish** veneer
- **FSC Certified**



Meranti Veneer

porta

- Real timber substrate

 The substrate is strong and durable timber.
- 2 Strong bond The bond strength of the veneer and substrate has been tested to AS/NZS 4266.33:2004.
- Premium finish veneer – Only premium grade timber veneer is used on the product face.

Timber Tips

Sanding

- It is recommended that you lightly sand before staining/ painting and between coats.
- Splice lines during the manufacturing process veneers are joined together so a fingerjoint may be seen on each piece. To eliminate the visibility you can sand before and between coats.
- A 240 grit sandpaper is recommended.

Fixing

 Pre-drill recommended to prevent splitting.



Architrave and Skirting Profiles

PROFILE		SPECIES	PORTA PRODUCT CODE	PRODUCT DETAILS/ DIMENSION	LENGTH
	Bullnose		BNA	42x12mm, 66x12mm, 66x18mm, 85x18mm	2.7m
	Bevelled		BVA	66x18mm	2.7m
	Colonial (TABMA AS.10)		COA	42x12mm, 66x12mm	2.7m
I	Colonial (TABMA AS.2)		COA	66x18mm, 85x18mm, 138x18mm	2.7m

Available in

Meranti Veneer



porta.com.au

people who know & love <mark>timber</mark>

